

SURFACE PREPARATION:

- **Cleaning:** Thoroughly clean all surfaces before applying Zero Rust.
- **New Steel:** Remove oil & mill scale before applying Zero Rust
- **Rusty Surfaces:** Remove all loose scale and powdery dust
- **Heavy Rust Scale:** Can be softened with the use of Prep-Step (™)
- **New Galvanized Steel:** Use a wash primer before applying Zero Rust

APPLICATION:

For best results apply two coats at 3 mils of wet film per coat allowing the product to flash a minimum of 20 minutes between coats. This will yield a total dry film thickness of approximately 3 mils which is necessary for optimum corrosion protection.

- **Thinning:** Always use VOC exempt solvents to thin Zero Rust
- **Drying Time:** Dries to touch in 30 minutes
- **Topcoats:** Many topcoats can be used. We suggest doing a test panel to determine compatibility
- **Clean up:** Always use VOC exempt solvents for your clean up of Zero Rust

DO NOT OVER APPLY!

Excess film will extend dry times dramatically and waste material with no improvement in corrosion resistance. To insure proper film thickness, measure with a wet film gauge.

Read the Zero Rust Application Guide prior to using Zero Rust.

For Technical Questions
800-725-4960



Maximum Rust Protection

Maximum Rust Protection



the ZERO RUST® color family includes:



60 Red Oxide



61 Gray



62 Black



63 Cat Yellow



67 White



68 Safety Blue




70 Green



71 Safety Yellow



72 Safety Red



95 Tan



The Zero Rust® colors displayed are best possible four color process printing representations of the actual Zero Rust family of colors and not meant as accurate color match samples.

AMTECO INCORPORATED
P.O. Box 9 • 1100 Jefferson Drive
Pacific, MO 63069
Phone: 800-969-4811
Technical line: 800-725-4960
www.amteco.com

Maximum Rust
PROTECTION



**STOPS
RUST NOW!**

**Rust and
Corrosion
Control
Coatings**

**HIGH PERFORMANCE
PRIMER**

ZERO RUST®

ZERO-RUST® is a DTM (direct to metal), phenolic modified alkyd rust and corrosion control coating, which puts down an impermeable barrier at the steel level. It's dielectric ability is extraordinary. Steel is isolated from the electrolysis process that converts steel to rust.

ZERO-RUST® is available in 12 oz. aerosol, quart, gallon and 5 gallon containers.

ZERO RUST® color selection:

- RED OXIDE
- GRAY
- BLACK
- CAT YELLOW
- WHITE
- SAFETY BLUE
- GREEN
- SAFETY YELLOW
- SAFETY RED
- TAN

as seen on
television's

**TRUCK
TV**

- ✓ DTM (direct to metal)
- ✓ SUPERIOR RUST CONTROL
- ✓ SINGLE-PACKAGE AIR DRY SYSTEM
- ✓ IMPERMEABLE BARRIER
- ✓ HIGH SOLIDS - LOW VOC
- ✓ LEAD & ISOCYANATE FREE
- ✓ TOPCOATS OPTIONAL
- ✓ 2000+ HOURS SALT SPRAY TEST RESULTS
- ✓ PROTECTION AT THE STEEL LEVEL
- ✓ NO SANDBLASTING REQUIRED
- ✓ EASY TO USE
- ✓ ENVIRONMENTALLY FRIENDLY
- ✓ COST EFFECTIVE

ZERO RUST® PROVIDES PROFESSIONAL STRENGTH RUST PROTECTION FOR YOUR NEXT HOME, FARM or GARDEN PROJECT:

DECORATIVE METAL FIXTURES:
*Patio Elements
Outdoor Metal
Yard Fixtures*



METAL COMPONENTS:
*Fencing, Shelving
Railings & Stairs*



AGRICULTURAL STRUCTURES and COMPONENTS:
*Barns, Cattle Chutes
Livestock Equipment*



METAL FURNITURE:
*Benches and Chairs
Tables and Work Areas*

